

Bray+Print

8065.01



product
Curtain

description
Floor-to-ceiling curtain+print black out with an non-directional weave structure

composition
100% flame retardant polyester acrylic coating

width
± 280 cm, ± 110 inches

weight
± 1075 gr/m², ± 35 oz/yd¹

visual & thermal comfort
EN 410/EN 14501

Test available
AATCC 148
Test available

flame retardant
NFPA 701 (meth. 1 or 2) , Pass
EN 13773 , Class 1
BS 5867-2 , Type B
DIN 4102 , B1
Übereinstimmung , Pass
UNI VF 8456-8457 , Classe 1
CAN/ULC S109 , Pass
IMO 2010 FTP part 7 , Pass

colorfastness crocking
ISO 105-X12
wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)
AATCC 8 (solids)
wet 5 (scale 1-5) / dry 5 (scale 1-5)

colorfastness to light

ISO 105-B02
5 (scale 1-8)
AATCC 16.2 option 1 or 16.3 opt 3
2.5 (scale 1-5)

seam slippage

ASTM D434 - warp
44 lbs
ASTM D434 - weft
49.5 lbs

labels



Baustoffklasse schwerentflammbar
DIN 4102, B1

care



Shrinkage

Shrinkage 30° - warp -0.9%
Shrinkage 30° - weft -0.6%
Shrinkage 70° - warp -1.5%
Shrinkage 70° - weft -1.2%

Bray+Print

8065.01



8065.01