


Carmen

8024.01 - 8024.09



product

Curtain

description

3-dimensional rib lengthwise with the brilliance of melting ice

composition

100% flame retardant polyester

width

± 150 cm, ± 59 inches

weight

± 136 gr/m², ± 4 oz/yd¹

sound absorption

ISO 354, alpha w

0.50 (pleated)

ASTM C423, nrc

0.30

visual & thermal comfort

EN 410/EN 14501

Test available

flame retardant

NFPA 701 (meth. 1 or 2) , Pass

EN 13773 , Class 1

BS 5867-2 , Type C

NF P 92/503-507 , M1

DIN 4102 , B1

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

CAN/ULC S109 , Pass

IMO 2010 FTP part 7 , Pass

colorfastness crocking

ISO 105-X12

wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)

AATCC 8 (solids)

wet 5 (scale 1-5) / dry 5 (scale 1-5)

colorfastness to light


ISO 105-B02

5 (scale 1-8)

AATCC 16.2 option 1 or 16.3 opt 3

4 (scale 1-5)

labels



Baustoffklasse schwerentflammbar
DIN 4102, B1

care



Shrinkage

Shrinkage 30° - warp -0.3%


Shrinkage 30° - weft -0.3%

Shrinkage 70° - warp -0.6%


Shrinkage 70° - weft -0.4%

Carmen

8024.01 - 8024.09



8024.01



8024.02




8024.03



8024.04




8024.05




8024.06



8024.07



8024.08



8024.09