

Tula

8081.01 - 8081.16



product

Curtain

description

Subtle coloured melange structure in a dry wooly look and feel

composition

60% recycled polyester FR / 40% polyester FR

width

± 149 cm, ± 59 inches

weight

± 395 gr/m², ± 13 oz/yd¹

sound absorption

ISO 354, alpha w

0.75 (pleated)

visual & thermal comfort

EN 410/EN 14501

Test available

flame retardant

NFPA 701 (meth. 1 or 2) , Pass

EN 13773 , Class 1

BS 5867-2 , Type C

NF P 92/503-507 , M1

DIN 4102 , B1

Übereinstimmung , Pass

UNI VF 8456-8457 , Classe 1

CAN/ULC S109 , Pass

IMO 2010 FTP part 7 , Pass

colorfastness crocking

ISO 105-X12

wet 4-5 (scale 1-5) / dry 4-5 (scale 1-5)

AATCC 8 (solids)

wet 5 (scale 1-5) / dry 5 (scale 1-5)

colorfastness to light

ISO 105-B02

6 (scale 1-8)

AATCC 16.2 option 1 or 16.3 opt 3

5 (scale 1-5)

seam slippage

ISO 13936-2 - warp

3 mm

ISO 13936-2 - weft

4.7 mm

ASTM D434 - warp

49 lbs

ASTM D434 - weft

51 lbs

labels



USCG -
EU MRA
0038



STANDARD
100
507-0023
Hohenstein HTTI



Baustoffklasse schwerentflammbar
DIN 4102, B1

care



Tula

Shrinkage

Shrinkage 70° - warp -2%

Shrinkage 70° - weft -1.6%



8081.01



8081.02



8081.03



8081.04



8081.05



8081.06



8081.07



8081.08



8081.09



8081.10



8081.11




8081.12



8081.13



8081.14



8081.15



8081.16